

# Mega metal

d.o.o.

## FLAIL TOPPER

UM 120 – UM 140 – UM 160 – UM 180 –  
UM 200 – UM 220

**Mega metal**  
d.o.o.

**HEADQUARTERS**

**ADDRESS:**

Varaždinska 45  
40305 Nedelišće  
CROATIA

**PRODUCTION FACILITY**

**ADDRESS:**

Sajmišna bb  
40329 Kotoriba  
CROATIA

**CONTACT INFORMATION:**

Tel.: + 385 040/682 -182

Tel./fax: + 385 040/821-108


Email: [megametal@ck.t-com.hr](mailto:megametal@ck.t-com.hr)  
[info@megametal.hr](mailto:info@megametal.hr)

**CEO:**

Tomica Novak



- Topper is intended for use in all agricultural surfaces, for maintenance of green areas and neglected fields.
- It can be used to mulch harvest waste material as well as branches up to 5 cm thick.
- The topper is of robust construction and is intended for intensive use.
- Topper is propelled from the tractor via cardan joint to reducer connection axis, from the transition axis to cogwheel in the reducer casing and through those to flails.



# Mega metal

d.o.o.

## STANDARD EQUIPMENT:

- Flails
- Lateral displacement - mechanical
- Gliders - sledge
- Adjustable by height
- Rear roller - adjustable by height
- Opening cover in the rear end of topper sheal to enable easier operation in difficult working conditions (for example mulching waste material)



## OPTIONAL EQUIPMENT:

- Front + rear connection
- Hydraulic offseting



## TEHNICAL DATA

MODEL	LEINGHT -cm	WIDTH -cm	HEIGHT -cm	NUMBERS OF FLAILS	OPERATIONAL WIDTH -cm	MIN. TRACTOR POWER KS KW	WEIGHT -KG
UM 120	93	140	86	12	120	25/18	325
UM 140	93	160	86	15	140	30/22	350
UM 160	93	180	86	15	160	35/25	378
UM 180	93	200	86	18	180	42/30	418
UM 200	93	220	86	21	200	50/36	458
UM 220	93	240	86	24	220	60/45	489