

Mega metal

d.o.o.

Mega metal
d.o.o.

HEADQUARTERS

ADDRESS:

Varaždinska 45
40305 Nedelišće
CROATIA

PRODUCTION FACILITY

ADDRESS:

Sajmišna bb
40329 Kotoriba
CROATIA

CONTACT INFORMATION:

Tel.: + 385 040/682 -182

Tel./fax: + 385 040/821-108

Email: megametal@ck.t-com.hr
info@megametal.hr

CEO:


Tomica Novak

FLAIL TOPPER

UMB 250 - 280



- Topper is intended for use in all agricultural surfaces, for maintenance of green areas and neglected fields.
- It can be used to mulch harvest waste material as well as branches up to 7 cm thick.
- The topper is of robust construction and is intended for intensive use.
- Topper is propelled from the tractor via cardan joint to reducer connection axis, from the transition axis to cogwheel in the reducer casing and through those to flails.



Mega metal

d.o.o.

STANDARD EQUIPMENT:

- Flails
- Lateral displacement - mechanical
- Gliders - sledge
- Adjustable by height
- Rear roller - adjustable by height
- Opening cover in the rear end of topper sheal to enable easier operation in difficult working conditions (for example mulching waste material)

OPTIONAL EQUIPMENT:

- Front + rear connection
- Hydraulic offseting



TEHKNICAL DATA

MODEL	LEINGHT -cm	WIDTH -cm	HEIGHT -cm	NUMBERS OF FLAILS	OPERATIONAL WIDTH -cm	MIN. TRACTOR POWER KS/KW	WEIGHT -KG
UMB 250	114	272	112	27	250	115/85	855
UMB 280	114	302	112	30	280	125/93	950